

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028086 A1**

(51) International Patent Classification<sup>7</sup>: **B01D 65/02**

(21) International Application Number:  
PCT/AU2004/001292

(22) International Filing Date:  
22 September 2004 (22.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003905174 22 September 2003 (22.09.2003) AU

(71) Applicant (for all designated States except US): **U.S. FILTER WASTEWATER GROUP, INC.** [US/US]; 181 Thorn Hill Road, Warrendale, PA 15086 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **JOHNSON, Warren, Thomas** [AU/AU]; 125 Grose Vale Road, Grose Vale, NSW 2753 (AU).

(74) Agent: **SHELSTON IP**; 60 Margaret Street, Sydney, NSW 2000 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**


— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

[Continued on next page]

(54) Title: **BACKWASH AND CLEANING METHOD**



(57) Abstract: A method of concentrating the solids of a liquid suspension by providing a pressure differential across the walls of permeable, hollow membranes (6) immersed in the liquid suspension (9). The liquid suspension (9) is applied to the outer surface of the porous hollow membranes (6) to induce and sustain filtration through the membrane walls (12) wherein some of the liquid suspension passes through the walls (12) of the membranes (6) to be drawn off as clarified liquid or permeate from the hollow membrane lumens (11), and at least some of the solids are retained on or in the hollow membranes (6) or otherwise as suspended solids within the liquid (9) surrounding the membranes (6). The method includes periodically backwashing the membrane pores using the permeate by applying a gas at a pressure below the bubble point to the membrane lumens (11) to progressively displace at least some of the liquid permeate within the lumens (11) through the membrane pores resulting in removal the solids retained on or in the hollow membranes into the bulk liquid (9) surrounding the membranes (6).



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*